

Grandstream Networks GRP2603 IP phone



Artikel	216310
Herstellernummer	GRP2603
EAN	6947273703181
Grandstream Networks	

Part of the GRP series of Carrier-Grade IP Phones, the GRP2603 is an essential 3-line model designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including: 5-way voice conferencing to maximize productivity, integrated PoE (GRP2603P), full HD audio on both the speaker and handset to allow users to communicate with the utmost clarity, EHS support for Plantronics, Jabra, and Sennheiser headsets and multi-language support.

Zusammenfassung

Part of the GRP series of Carrier-Grade IP Phones, the GRP2603 is an essential 3-line model designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including: 5-way voice conferencing to maximize productivity, integrated PoE (GRP2603P), full HD audio on both the speaker and handset to allow users to communicate with the utmost clarity, EHS support for Plantronics, Jabra, and Sennheiser headsets and multi-language support.

Grandstream Networks GRP2603, IP Phone, Black, 3 lines, LCD, 6.3 cm (2.48"), Fast Ethernet

Grandstream Networks GRP2603. Product type: IP Phone, Product colour: Black. Lines quantity: 3 lines. Display: LCD, Display diagonal: 6.3 cm (2.48"). Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Supported network protocols: SIP RFC3261, TCP/IP/UDP, RTP/RTCP, RTCP-XR, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR),.... AC adapter input voltage: 100-240 V, Input frequency: 50/60 Hz

Merkmale

Packaging content

Number of handles included 1 pc(s)

Ports & interfaces

RJ-9 ports quantity 1

Design

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-10 - 60 °C

Weight & dimensions

Width	206 mm
Depth	214 mm
Height	68 mm

Product type	IP Phone
Product colour	Black

Display

Display	LCD
Display diagonal	6.3 cm (2.48")

Power

AC adapter input voltage	100-240 V
Input frequency	50/60 Hz

Network

Ethernet LAN	Yes
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Supported network protocols	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, RTCP-XR, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR- 069, SNMP, 802.1x, TLS, SRTP, IPv6

Phone features

Lines quantity	3 lines
Call waiting	Yes
Call hold	Yes
Call forwarding	Yes

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.