

Yealink W70B DECT base station



Artikel	224870
Herstellernummer	W70B
EAN	6938818307254
Yealink	

High-performance DECT IP base station for small and medium-sized businesses

The Yealink W70B is the DECT IP base station for small and medium-sized businesses. Paring with up to a total of 10 Yealink W73H/W56H/W59R/CP930W/color screen DDPHONE (T54W+DD10K) DECT handsets, W70B allows you to enjoy superb mobility and efficient flexibility immediately as well as significantly eliminates additional wiring troubles and charges. A powerful chip ensuring a better and higher performance, this DECT IP base station not only supports up to 10 VoIP accounts and 20 simultaneous calls, but also speeds up its startup and signal connection, provides no perception upgrade, slashes its upgrade downtime as well.

Designed in modern and elegant style, this compact DECT IP base station possesses a wire-hidden design, presenting a concise and tidy desk to you even being mounted to the wall. By supporting Opus codec, Yealink W70B consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions, comparing with other wideband or narrowband audio

The Yealink W70B DECT IP base station supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes it simple to deploy, easy to maintain and upgrade, saving even more time and IT costs for businesses

Zusammenfassung

High-performance DECT IP base station for small and medium-sized businesses

The Yealink W70B is the DECT IP base station for small and medium-sized businesses. Paring with up to a total of 10 Yealink W73H/W56H/W59R/CP930W/color screen DDPHONE (T54W+DD10K) DECT handsets, W70B allows you to enjoy superb mobility and efficient flexibility immediately as well as significantly eliminates additional wiring troubles and charges. A powerful chip ensuring a better and higher performance, this DECT IP base station not only supports up to 10 VoIP accounts and 20 simultaneous calls, but also speeds up its startup and signal connection, provides no perception upgrade, slashes its upgrade downtime as well.

Designed in modern and elegant style, this compact DECT IP base station possesses a wire-hidden design, presenting a concise and tidy desk to you even being mounted to the wall. By supporting Opus codec, Yealink W70B consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions, comparing with other wideband or narrowband audio

The Yealink W70B DECT IP base station supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes it simple to deploy, easy to maintain and upgrade, saving even more time and IT costs for businesses

Yealink W70B, 300 m, SNTP/NTP, UDP/TCP/TLS, AES, HTTPS, SHA-256, SHA-384, SHA-512, TLS, CAT-iq2.0, AGC, AJB, AMR-WB, CNG, G.722, G.726, G.729, G.729A, PLC, VAD, iLBC, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3af

Yealink W70B. Maximum range: 300 m, Management protocols: SNTP/NTP, UDP/TCP/TLS, Security algorithms: AES, HTTPS, SHA-256, SHA-384, SHA-512, TLS. Phonebook capacity (per handset): 1000 entries. Frequency range (EU): 1880 - 1900 MHz,

Frequency range (US): 1920 - 1930 MHz. Ethernet LAN data rate supported (max): 100 Mbit/s. Product colour: Grey, Certification: CE, FCC, REACH

Merkmale

Antenna

Frequency range (EU)	1880 - 1900 MHz
Frequency range (US)	1920 - 1930 MHz

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-10 - 95% H)	

Packaging content

Quick start guide	Y
Power adapter included	Y

Ports & interfaces

Ethernet LAN	Y
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rate supported (max)	100 Mbit/s

Power

Input voltage	100 - 240 V
Output voltage	5 V
Output current	0.6 A

Design

Product colour	Grey
Full duplex	Y
Wall mountable	Y
LED indicators	Y
Certification	CE, FCC, REACH

Weight & dimensions

Dimensions (WxDxH)	130 x 100 x 25.1 mm
Weight	3.61 kg
Package width	174 mm
Package depth	180 mm
Package height	63 mm
Package weight	4.15 kg

Performance

Number of handsets supported (max)	10
Maximum range	300 m
CAT-iq	2.0
Number of VoIP accounts	10
Management protocols	SNTP/NTP, UDP/TCP/TLS
Security algorithms	AES, HTTPS, SHA-256, SHA-384, SHA-512, TLS
DECT standards	CAT-iq2.0
Voice codecs	AGC, AJB, AMR-WB, CNG, G.722, G.726, G.729, G.729A, PLC, VAD, iLBC
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3af
Hearing aid compatibility	Y
Music on hold function	Y
XML browser	Y
Auto-provision	Y

Call management

Conference call	Y
Number of parallel conferences	3
Phonebook capacity (per handset)	1000 entries
Number of simultaneous calls (max)	20
Anonymous call	Y
Anonymous call rejection	Y
Call waiting	Y
Call forwarding	Y
Caller ID	Y
Remote phonebook	Y
Call transfer	Y
Call hold	Y
Switching between calls	Y

Mute function	Y
Speed dialling	Y
Integrated voicemail	Y
Redialing	Y
Message Waiting Indication (MWI) function	Y
Phonebook search/import/export function	Y
Call history	Y
Reset function	Y
Emergency call	Y
Shared Call Appearance (SCA)	Y
System log export	Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.