

Thermaltake TT TH240 ARGB

Artikel	245175
Herstellernummer	CL-W361-PL12SW-A
EAN	0841163087909
Thermaltake	



TH240 V2 ARGB has a new industrial cap with an infinity mirror light design, bringing a new vibe to the TH series. Equipped with two CT120 ARGB fans, the TH240 V2 ARGB is suitable for small to medium chassis that fit 240mm AIOs, and for those who seek to control lighting effects through 5V motherboard-controlled software.

New Version, New Design

TH V2 ARGB was given an industrial look to freshen up the 360-degree rotational cap. Adding Infinity Mirror Lighting to this series can bring more diverse visual effects to the build and gives more depth than it looks.

Enhanced Cooling Surface With A Compact Design

The TH V2 ARGB Series has a 27mm slim radiator with a thickened 20mm copper chamber, ensuring the same easy installation but with even better cooling performance.

Less Cables, Less Mess

The new cable-integrated daisy-chain design allows the fans to be directly connected, so it minimizes demands of 4-pin PWM and 3-pin ARGB ports on your motherboard and shortens the cable length between the fans. We've also included one 900mm PWM cables and one 900mm ARGB cable for you to easily manage your cables while assembling your build.

Keeping Your Cables in Place

You might have experienced easily detached 5V ARGB cables when you assemble your builds. Worry not; this 5V ARGB Connector Clip can guarantee that the cables are correctly connected and won't get loose in unexpected conditions.

Keep it COLD with Copper

The high-performance copper base plate accelerates heat conductivity. The high-quality and reliable pump enables maximum water circulation, keeping the copper plate continuously cool. The low evaporation tube effectively decreases the loss of coolant; therefore, no refill is required.

Any CPU Can Be the Right CPU

The package includes brackets for the latest Intel and AMD CPU sockets to be compatible with the most modern CPU platforms, including the latest Intel LGA1700 and AMD AM5 CPUs.

Sync with Motherboard RGB Software

Designed to synchronize with ASUS Aura Sync, GIGABYTE RGB Fusion, MSI Mystic Light Sync, and ASRock Polychrome. It supports motherboards with a 5V addressable RGB header, allowing you to control the lights directly from the software mentioned above without installing any extra lighting software or controllers. For more details, please visit ASUS, GIGABYTE, MSI, and ASRock official websites.

Zusammenfassung

TH240 V2 ARGB has a new industrial cap with an infinity mirror light design, bringing a new vibe to the TH series. Equipped with two CT120 ARGB fans, the TH240 V2 ARGB is suitable for small to medium chassis that fit 240mm AIOs, and for those who seek to control lighting effects through 5V motherboard-controlled software.

New Version, New Design

TH V2 ARGB was given an industrial look to freshen up the 360-degree rotational cap. Adding Infinity Mirror Lighting to this series can bring more diverse visual effects to the build and gives more depth than it looks.

Enhanced Cooling Surface With A Compact Design

The TH V2 ARGB Series has a 27mm slim radiator with a thickened 20mm copper chamber, ensuring the same easy installation but with even better cooling performance.

Less Cables, Less Mess

The new cable-integrated daisy-chain design allows the fans to be directly connected, so it minimizes demands of 4-pin PWM and 3-pin ARGB ports on your motherboard and shortens the cable length between the fans. We've also included one 900mm PWM cables and one 900mm ARGB cable for you to easily manage your cables while assembling your build.

Keeping Your Cables in Place

You might have experienced easily detached 5V ARGB cables when you assemble your builds. Worry not; this 5V ARGB Connector Clip can guarantee that the cables are correctly connected and won't get loose in unexpected conditions.

Keep it COLD with Copper

The high-performance copper base plate accelerates heat conductivity. The high-quality and reliable pump enables maximum water circulation, keeping the copper plate continuously cool. The low evaporation tube effectively decreases the loss of coolant; therefore, no refill is required.

Any CPU Can Be the Right CPU

The package includes brackets for the latest Intel and AMD CPU sockets to be compatible with the most modern CPU platforms, including the latest Intel LGA1700 and AMD AM5 CPUs.

Sync with Motherboard RGB Software

Designed to synchronize with ASUS Aura Sync, GIGABYTE RGB Fusion, MSI Mystic Light Sync, and ASRock Polychrome. It supports motherboards with a 5V addressable RGB header, allowing you to control the lights directly from the software mentioned above without installing any extra lighting software or controllers. For more details, please visit ASUS, GIGABYTE, MSI, and ASRock official websites.

Thermaltake TT TH240 ARGB, All-in-one liquid cooler, 12 cm, 1500 RPM, 3300 RPM, Black

Thermaltake TT TH240 ARGB. Type: All-in-one liquid cooler, Fan diameter: 12 cm, Rotational speed (min): 1500 RPM, Rotational speed (max): 3300 RPM, Maximum air pressure: 2.23 mmH2O, Bearing type: Hydraulic. Voltage: 12 V. Product colour: Black

Merkmale

		Power	
Logistics data		Voltage	12 V
Harmonized System (HS) code84733080		Rated voltage	5 V
		Pump voltage	12/5 V
		Pump current	430 mA
		Fan current	0.38 A
Other features		Weight & dimensions	
Tube material	Rubber	Radiator width	27.6 cm
Design		Radiator depth	12 cm
		Radiator height	2.7 cm
		Tube length	46 cm
		Fan dimensions (W x D x H)	120 x 120 x 25 mm
		Performance	
Product colour	Black	Suitable location	Processor
Material	Aluminium		
Number of fans	2 fan(s)		
Fan connector	3-pin		
Water block material	Copper		

Type	All-in-one liquid cooler
Fan diameter	12 cm
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM1, Socket FM2
Rotational speed (min)	1500 RPM
Rotational speed (max)	3300 RPM
Maximum airflow	57.05 cfm
Maximum air pressure	2.23 mmH2O
Bearing type	Hydraulic
Fan noise level (max)	25.8 dB
Quantity per pack	1 pc(s)
Pump motor speed (min)	1500 RPM
Pump motor speed (max)	3300 RPM
Fan speed (min)	500 RPM
Fan speed (max)	2000 RPM

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.