

Honeywell MS9540 VoyagerCG



Artikel	299392
Herstellernummer	MK9540-37A38
EAN	5711045269240
Honeywell	

Voyager and VoyagerCG hand-held, single-line laser scanners feature patented automatic infrared activation and decode all standard 1D bar codes, including GS1 DataBar™. VoyagerCG also includes CodeGate® technology for menu scanning applications. CodeGate zeroes in on the desired code and completes data transmission with the push of a single button.

- Automatic trigger: Use scanner as either a hand-held device or a fixed presentation scanner when mounted in the stand
- CodeGate® data transmission: Ideal for menu-scanning applications and when combined with the Auto-Trigger, VoyagerCG® is the most intuitive bar code scanning system in the industry
- 650-nanometer laser: Equipped with a high-visibility laser allowing the user to place the line on bar code
- FlashROM: Update firmware from any PC via MetroSet®2 software provided free from Metrologic
- Parsing (data editing): Bar code data can be formatted to meet the requirements of host system

Zusammenfassung

Voyager and VoyagerCG hand-held, single-line laser scanners feature patented automatic infrared activation and decode all standard 1D bar codes, including GS1 DataBar™. VoyagerCG also includes CodeGate® technology for menu scanning applications. CodeGate zeroes in on the desired code and completes data transmission with the push of a single button.

- Automatic trigger: Use scanner as either a hand-held device or a fixed presentation scanner when mounted in the stand
- CodeGate® data transmission: Ideal for menu-scanning applications and when combined with the Auto-Trigger, VoyagerCG® is the most intuitive bar code scanning system in the industry
- 650-nanometer laser: Equipped with a high-visibility laser allowing the user to place the line on bar code
- FlashROM: Update firmware from any PC via MetroSet®2 software provided free from Metrologic
- Parsing (data editing): Bar code data can be formatted to meet the requirements of host system

Honeywell MS9540 VoyagerCG, 1D, Laser, 0 - 4842 lx, 650 nm, USB, Black

Honeywell MS9540 VoyagerCG. Scanner type: 1D, Sensor type: Laser, Light levels (direct sunlight): 0 - 4842 lx. Standard interfaces: USB. Product colour: Black, Certification: FCC Part 15, ICES-003, EN55022 Class B. Input voltage: 5 V. Weight: 149 g, Width: 78 mm, Depth: 198 mm

Merkmale

Operational conditions

Logistics data

Harmonized System (HS) code	84716070
-----------------------------	----------

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	5 - 95%

Ports & interfaces

Standard interfaces	USB
---------------------	-----

Scanning

Scanner type	1D
Sensor type	Laser
Light levels (direct sunlight)	0 - 4842 lx
Wavelength	650 nm

Power

Input voltage	5 V
---------------	-----

Weight & dimensions

Width	78 mm
Depth	198 mm
Height	56 mm
Weight	149 g

Performance

Product colour	Black
Certification	FCC Part 15, ICES-003, EN55022 Class B

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.