

Inter-Tech Argus APS power supply unit



Artikel	300805
Herstellernummer	88882116
EAN	4260133126008
Inter-Tech	

- The Argus APS-420W – ideal for sophisticated office solutions
- The Argus APS-420W provides the customers with a high efficiency of at least 82% and therefore protects environment and wallet.
- Thanks to the efficient construction and the ideal configured connector layout the APS-420W provides with sufficient performance for the connected components.
- The yellow 120mm fan works silently and ensures an optimal cooling of the power supply.

Zusammenfassung

- The Argus APS-420W – ideal for sophisticated office solutions
- The Argus APS-420W provides the customers with a high efficiency of at least 82% and therefore protects environment and wallet.
- Thanks to the efficient construction and the ideal configured connector layout the APS-420W provides with sufficient performance for the connected components.
- The yellow 120mm fan works silently and ensures an optimal cooling of the power supply.

Inter-Tech Argus APS, 420 W, 115 - 230 V, 47 - 63 Hz, +12V1,+12V2,+3.3V,+5V,+5Vsb,-12V, Active, 103 W

Inter-Tech Argus APS. Total power: 420 W, AC input voltage: 115 - 230 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, Noise level: 21 dB. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm

Merkmale

Logistics data

Harmonized System (HS) code 84733020

Performance

Purpose PC
Power supply unit (PSU) form ATX

Packaging data

Manual	Y
Package width	240 mm
Package depth	95 mm
Package height	170 mm
Package weight	1.42 kg
Package type	Box

Ports & interfaces

factor	
ATX version	2.31
Noise level	21 dB

Weight & dimensions

Width	150 mm
Depth	140 mm
Height	86 mm
Weight	1.1 kg

Design

Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
Fan location	Top
On/off switch	Y

Motherboard power connector	20+4 pin ATX
Number of SATA power connectors	3
Peripheral (Molex) power connectors (4-pin)	2
CPU power connector (4+4 pin)	Y
ATX power connector (20+4 pin)	Y
Floppy drive power connector	1
Floppy disk drive connector	Y
Cabling type	Non-Modular

Power

Total power	420 W
AC input voltage	115 - 230 V
AC input frequency	47 - 63 Hz
Maximum input current (@110V)	+12V1,+12V2,+3.3V,+5V,+5Vsb,-12V
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	103 W
Combined power (+5V)	103 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	15 A
Max output current (+12V1)	17 A
Max output current (+12V2)	18 A
Max output current (+5V)	15 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.