

Chieftec PSF-400B power supply unit



Artikel	318889
Herstellernummer	PSF-400B
EAN	4710713234499
Chieftec	

The PSF-400B from its layout may remind on “fore gone” ATX standards but, compatible with all current standards and certified by TÜV amongst many others and with a fixed voltage of 230V being the European standard, the PSF-400B is a reliable and efficient companion for modern IT structures which thereby also fulfills all ENERGY STAR 5.0 requirements as stipulated by the EU.

Dedicated majorly to the 19” IPC / UNC solutions ranging between 2U ~ 4U where the PSU position is delicate and/or tricky and the cooling fan MUST blow out the rear owing to highly limited height issues of the related chassis.

Zusammenfassung

The PSF-400B from its layout may remind on “fore gone” ATX standards but, compatible with all current standards and certified by TÜV amongst many others and with a fixed voltage of 230V being the European standard, the PSF-400B is a reliable and efficient companion for modern IT structures which thereby also fulfills all ENERGY STAR 5.0 requirements as stipulated by the EU.

Dedicated majorly to the 19” IPC / UNC solutions ranging between 2U ~ 4U where the PSU position is delicate and/or tricky and the cooling fan MUST blow out the rear owing to highly limited height issues of the related chassis.

Chieftec PSF-400B, 400 W, 100 - 240 V, 47 - 63 Hz, Active, 100 W, 360 W

Chieftec PSF-400B. Total power: 400 W, AC input voltage: 100 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 45 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Metallic, Cooling type: Active, Fan diameter: 8 cm. Compliance certificates: RoHS

Merkmale

Certificates

Compliance certificates RoHS

Performance

80 PLUS certification	80 PLUS Bronze
Purpose	PC
Power supply unit (PSU) form factor	ATX
ATX version	2.3

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------

Technical details

Sustainability certificates	ENERGY STAR
-----------------------------	-------------

Weight & dimensions

Width	150 mm
Depth	140 mm
Height	87 mm

Design

Product colour	Metallic
Cooling type	Active
Fan diameter	8 cm
Number of fans	1 fan(s)
Fan location	Side

Ports & interfaces

Motherboard power connector	24-pin ATX
Motherboard power cable length	45 cm
Number of SATA power connectors	4
Peripheral (Molex) power connectors (4-pin)	3
EPS power connector (8-pin)	Yes
PCI Express power connectors (6-pin)	1
Floppy drive power connector	1
Cabling type	Non-Modular

Power

Total power	400 W
AC input voltage	100 - 240 V
AC input frequency	47 - 63 Hz
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (+12V)	360 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	12.5 W
Max output current (+3.3V)	16 A
Max output current (+12V1)	30 A
Max output current (+5V)	15 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	2.5 A
Efficiency	87%
Power protection features	Overload, Short circuit

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.