

TP-Link TL-SG1008P

Artikel
Herstellernummer
EAN
TP-Link

371239
TL-SG1008P V3
6935364021160



PoE Switches for Your Ultra Convenience 8-Port Gigabit Desktop Switch with 4-Port PoE

Power over Ethernet

4 of the 5 Auto-Negotiation RJ45 ports (Port 1 to Port 4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs).

Intelligent Power Management

When total power consumption exceeds 55W, the intelligent power management will cut the lower priority port power off to ensure the high priority port's power supply and protect the device from power overload operation.

Sturdy Metal Casing

Sturdy, compact metal casing and shielded RJ45 ports, with desktop, to meet your needs in any environment. Besides, fanless design ensures quiet operation.

Zusammenfassung

PoE Switches for Your Ultra Convenience 8-Port Gigabit Desktop Switch with 4-Port PoE

Power over Ethernet

4 of the 5 Auto-Negotiation RJ45 ports (Port 1 to Port 4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs).

Intelligent Power Management

When total power consumption exceeds 55W, the intelligent power management will cut the lower priority port power off to ensure the high priority port's power supply and protect the device from power overload operation.

Sturdy Metal Casing

Sturdy, compact metal casing and shielded RJ45 ports, with desktop, to meet your needs in any environment. Besides, fanless design ensures quiet operation.

TP-Link 8-Port Gigabit Desktop PoE Switch with 4-Port, Gigabit Ethernet (10/100/1000), Power over Ethernet (PoE)

TP-Link 8-Port Gigabit Desktop PoE Switch with 4-Port. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 4000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in

jack. Power over Ethernet (PoE)

Merkmale

Data transmission

Switching capacity	16 Gbit/s
MAC address table	4000 entries
Store-and-forward	Y

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Y
Power over Ethernet (PoE) ports quantity	4
Total Power over Ethernet (PoE) budget	55 W

Weight & dimensions

Width	171 mm
Depth	98 mm
Height	27 mm

Design

Rack mounting	N
Product colour	Grey
LED indicators	Y
Certification	CE, FCC, RoHS

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-10 - 90% H)	
Storage relative humidity (H-5 - 90% H)	

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	8
Power connector	DC-in jack

Packaging data

Cables included	AC
User guide	Y
Package type	Box
Package width	280 mm
Package depth	223 mm
Package height	68 mm

Power

Power source	DC
Power supply included	Y
Number of power supply units	1
Input current	1.25 A
Input voltage	48 V
Power consumption (max)	65.24 W

Network

Networking standards	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support	N
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T
Flow control support	Y
Auto MDI/MDI-X	Y
Auto-negotiation	Y
MAC address auto-learning supported	Y
MAC address auto-aging supported	Y

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.