Intel Xeon Silver 4410Y processor



Artikel Herstellernummer EAN Intel 417728 PK8071305120002 8592978435424

Intel® Trusted Execution Technology

Intel® Trusted Execution Technology for safer computing is a versatile set of hardware extensions to Intel® processors and chipsets that enhance the digital office platform with security capabilities such as measured launch and protected execution. It enables an environment where applications can run within their own space, protected from all other software on the system.

Intel® Virtualization Technology for Directed I/O (VT-d)

Intel® Virtualization Technology for Directed I/O (VT-d) continues from the existing support for IA-32 (VT-x) and Itanium® processor (VT-i) virtualization adding new support for I/O-device virtualization. Intel VT-d can help end users improve security and reliability of the systems and also improve performance of I/O devices in virtualized environments.

Intel® Virtualization Technology (VT-x)

Intel® Virtualization Technology (VT-x) allows one hardware platform to function as multiple "virtual" platforms. It offers improved manageability by limiting downtime and maintaining productivity by isolating computing activities into separate partitions.

Intel® 64

Intel® 64 architecture delivers 64-bit computing on server, workstation, desktop and mobile platforms when combined with supporting software.¹ Intel 64 architecture improves performance by allowing systems to address more than 4 GB of both virtual and physical memory.

Cache

CPU Cache is an area of fast memory located on the processor. Intel® Smart Cache refers to the architecture that allows all cores to dynamically share access to the last level cache.

Intel® AES New Instructions

Intel® AES New Instructions (Intel® AES-NI) are a set of instructions that enable fast and secure data encryption and decryption. AES-NI are valuable for a wide range of cryptographic applications, for example: applications that perform bulk encryption/decryption, authentication, random number generation, and authenticated encryption.

Intel® Turbo Boost Technology

Intel® Turbo Boost Technology dynamically increases the processor's frequency as needed by taking advantage of thermal and power headroom to give you a burst of speed when you need it, and increased energy efficiency when you don't.

Max Turbo Frequency

Max Turbo Frequency is the maximum single-core frequency at which the processor is capable of operating using Intel® Turbo Boost Technology and, if present, Intel® Turbo Boost Max Technology 3.0 and Intel® Thermal Velocity Boost. Frequency is typically measured in gigahertz (GHz), or billion cycles per second.

Execute Disable Bit

Execute Disable Bit is a hardware-based security feature that can reduce exposure to viruses and malicious-code attacks and

prevent harmful software from executing and propagating on the server or network.

Intel® Hyper-Threading Technology

Intel® Hyper-Threading Technology (Intel® HT Technology) delivers two processing threads per physical core. Highly threaded applications can get more work done in parallel, completing tasks sooner.

Intel® VT-x with Extended Page Tables (EPT)

Intel® VT-x with Extended Page Tables (EPT), also known as Second Level Address Translation (SLAT), provides acceleration for memory intensive virtualized applications. Extended Page Tables in Intel® Virtualization Technology platforms reduces the memory and power overhead costs and increases battery life through hardware optimization of page table management.

Intel® Speed Shift Technology

Intel® Speed Shift Technology uses hardware-controlled P-states to deliver dramatically quicker responsiveness with singlethreaded, transient (short duration) workloads, such as web browsing, by allowing the processor to more quickly select its best operating frequency and voltage for optimal performance and power efficiency.

Intel® Crypto Acceleration

Intel® Crypto Acceleration reduces the performance impact of pervasive encryption and increases the performance of encryptionintensive workloads including SSL web serving, 5G infrastructure, and VPN/firewalls.

Intel® Software Guard Extensions (Intel® SGX)

Intel® Software Guard Extensions (Intel® SGX) provide applications the ability to create hardware enforced trusted execution protection for their applications' sensitive routines and data. Intel® SGX provides developers a way to partition their code and data into CPU hardened trusted execution environments (TEE's).

Intel® Deep Learning Boost (Intel® DL Boost)

A new set of embedded processor technologies designed to accelerate AI deep learning use cases. It extends Intel AVX-512 with a new Vector Neural Network Instruction (VNNI) that significantly increases deep learning inference performance over previous generations.

Instruction Set Extensions

Instruction Set Extensions are additional instructions which can increase performance when the same operations are performed on multiple data objects. These can include SSE (Streaming SIMD Extensions) and AVX (Advanced Vector Extensions).

Intel® Total Memory Encryption

TME – Total Memory Encryption (TME) helps protect data against exposure via physical attack on memory, such as cold-boot attacks.

Max # of UPI Links

Intel® Ultra Path Interconnect (UPI) links are a high speed, point-to-point interconnect bus between the processors, delivering increased bandwidth and performance over Intel® QPI.

of AVX-512 FMA Units

Intel® Advanced Vector Extensions 512 (AVX-512), new instruction set extensions, delivering ultra-wide (512-bit) vector operations capabilities, with up to 2 FMAs (Fused Multiply Add instructions), to accelerate performance for your most demanding computational tasks.

Intel® Resource Director Technology (Intel® RDT)

Intel® RDT brings new levels of visibility and control over how shared resources such as last-level cache (LLC) and memory bandwidth are used by applications, virtual machines (VMs) and containers.

Intel® Speed Select Technology - Performance Profile

A capability to configure the processor to run at three distinct operating points.

Mode-based Execute Control (MBEC)

Mode-based Execute Control can more reliably verify and enforce the integrity of kernel level code.

Intel® Boot Guard

Intel® Device Protection Technology with Boot Guard helps protect the system's pre-OS environment from viruses and malicious software attacks.

Intel® Control-Flow Enforcement Technology

CET - Intel Control-flow Enforcement Technology (CET) helps protect against the misuse of legitimate code snippets through returnoriented programming (ROP) control-flow hijacking attacks.

Intel® Transactional Synchronization Extensions

Intel® Transactional Synchronization Extensions (Intel® TSX) are a set of instructions that add hardware transactional memory support to improve performance of multi-threaded software.

Zusammenfassung

Intel® Trusted Execution Technology

Intel® Trusted Execution Technology for safer computing is a versatile set of hardware extensions to Intel® processors and chipsets that enhance the digital office platform with security capabilities such as measured launch and protected execution. It enables an environment where applications can run within their own space, protected from all other software on the system.

Intel® Virtualization Technology for Directed I/O (VT-d)

Intel® Virtualization Technology for Directed I/O (VT-d) continues from the existing support for IA-32 (VT-x) and Itanium® processor (VT-i) virtualization adding new support for I/O-device virtualization. Intel VT-d can help end users improve security and reliability of the systems and also improve performance of I/O devices in virtualized environments.

Intel® Virtualization Technology (VT-x)

Intel® Virtualization Technology (VT-x) allows one hardware platform to function as multiple "virtual" platforms. It offers improved manageability by limiting downtime and maintaining productivity by isolating computing activities into separate partitions.

Intel® 64

Intel® 64 architecture delivers 64-bit computing on server, workstation, desktop and mobile platforms when combined with supporting software.¹ Intel 64 architecture improves performance by allowing systems to address more than 4 GB of both virtual and physical memory.

Cache

CPU Cache is an area of fast memory located on the processor. Intel® Smart Cache refers to the architecture that allows all cores to dynamically share access to the last level cache.

Intel® AES New Instructions

Intel® AES New Instructions (Intel® AES-NI) are a set of instructions that enable fast and secure data encryption and decryption. AES-NI are valuable for a wide range of cryptographic applications, for example: applications that perform bulk encryption/decryption, authentication, random number generation, and authenticated encryption.

Intel® Turbo Boost Technology

Intel® Turbo Boost Technology dynamically increases the processor's frequency as needed by taking advantage of thermal and power headroom to give you a burst of speed when you need it, and increased energy efficiency when you don't.

Max Turbo Frequency

Max Turbo Frequency is the maximum single-core frequency at which the processor is capable of operating using Intel® Turbo Boost Technology and, if present, Intel® Turbo Boost Max Technology 3.0 and Intel® Thermal Velocity Boost. Frequency is typically measured in gigahertz (GHz), or billion cycles per second.

Execute Disable Bit

Execute Disable Bit is a hardware-based security feature that can reduce exposure to viruses and malicious-code attacks and prevent harmful software from executing and propagating on the server or network.

Intel® Hyper-Threading Technology

Intel® Hyper-Threading Technology (Intel® HT Technology) delivers two processing threads per physical core. Highly threaded applications can get more work done in parallel, completing tasks sooner.

Intel® VT-x with Extended Page Tables (EPT)

Intel® VT-x with Extended Page Tables (EPT), also known as Second Level Address Translation (SLAT), provides acceleration for memory intensive virtualized applications. Extended Page Tables in Intel® Virtualization Technology platforms reduces the memory and power overhead costs and increases battery life through hardware optimization of page table management.

Intel® Speed Shift Technology

Intel® Speed Shift Technology uses hardware-controlled P-states to deliver dramatically quicker responsiveness with single-threaded, transient (short duration) workloads, such as web browsing, by allowing the processor to more quickly select its best operating frequency and voltage for optimal performance and power efficiency.

Intel® Crypto Acceleration

Intel® Crypto Acceleration reduces the performance impact of pervasive encryption and increases the performance of encryptionintensive workloads including SSL web serving, 5G infrastructure, and VPN/firewalls.

Intel® Software Guard Extensions (Intel® SGX)

Intel® Software Guard Extensions (Intel® SGX) provide applications the ability to create hardware enforced trusted execution protection for their applications' sensitive routines and data. Intel® SGX provides developers a way to partition their code and data into CPU hardened trusted execution environments (TEE's).

Intel® Deep Learning Boost (Intel® DL Boost)

A new set of embedded processor technologies designed to accelerate AI deep learning use cases. It extends Intel AVX-512 with a new Vector Neural Network Instruction (VNNI) that significantly increases deep learning inference performance over previous generations.

Instruction Set Extensions

Instruction Set Extensions are additional instructions which can increase performance when the same operations are performed on multiple data objects. These can include SSE (Streaming SIMD Extensions) and AVX (Advanced Vector Extensions).

Intel® Total Memory Encryption

TME – Total Memory Encryption (TME) helps protect data against exposure via physical attack on memory, such as cold-boot attacks.

Max # of UPLL inks

Intel® Ultra Path Interconnect (UPI) links are a high speed, point-to-point interconnect bus between the processors, delivering increased bandwidth and performance over Intel® QPI.

of AVX-512 FMA Units

Intel® Advanced Vector Extensions 512 (AVX-512), new instruction set extensions, delivering ultra-wide (512-bit) vector operations capabilities, with up to 2 FMAs (Fused Multiply Add instructions), to accelerate performance for your most demanding computational tasks.

Intel® Resource Director Technology (Intel® RDT)

Intel® RDT brings new levels of visibility and control over how shared resources such as last-level cache (LLC) and memory bandwidth are used by applications, virtual machines (VMs) and containers.

Intel® Speed Select Technology - Performance Profile

A capability to configure the processor to run at three distinct operating points.

Mode-based Execute Control (MBEC)

Mode-based Execute Control can more reliably verify and enforce the integrity of kernel level code.

Intel® Boot Guard

Intel® Device Protection Technology with Boot Guard helps protect the system's pre-OS environment from viruses and malicious software attacks.

Intel® Control-Flow Enforcement Technology

CET - Intel Control-flow Enforcement Technology (CET) helps protect against the misuse of legitimate code snippets through returnoriented programming (ROP) control-flow hijacking attacks.

Intel® Transactional Synchronization Extensions

Intel® Transactional Synchronization Extensions (Intel® TSX) are a set of instructions that add hardware transactional memory support to improve performance of multi-threaded software.

Intel Xeon Silver 4410Y, Intel Xeon Silver, LGA 4677 (Socket E), Intel, 4410Y, 2 GHz, Intel Xeon Scalable 4th Gen

Intel Xeon Silver 4410Y. Processor family: Intel Xeon Silver, Processor socket: LGA 4677 (Socket E), Processor manufacturer: Intel. Memory channels: Octa-channel, Maximum internal memory supported by processor: 6 TB, Memory types supported by processor: DDR4-SDRAM. Market segment: Server, Use conditions: Server/Enterprise, Supported instruction sets: AMX, SSE4.2, AVX, AVX 2.0, AVX-512. Maximum Enclave Size Support for Intel® SGX: 64 GB, Intel® Data Streaming Accelerator (DSA): 1 default devices. Package type: Retail box

Merkmale

Memory

Logistics data

Maximum internal memory supported by processor

6 TB

Harmonized System (HS) code	8542310001	Memory types supported by processor	DDR4-SDRAM
		Memory channels	Octa-channel
		ECC	Yes
Other features			
Maximum internal memory	4 TB	Technical details	
		Launch date	Q1'23
Packaging data		Status	Launched
3 3		Supported memory types	DDR4-SDRAM
Package type	Retail box	Memory speed (max)	4000 MHz
		Number of UPI links	2
		Package carrier	E1B
Weight & dimensions			
Processor package size	77.5 x 56.5 mm	Features	
		Execute Disable Bit	Yes
			163
		Market segment	Server
Operational conditions	S		
-		Market segment Use conditions Maximum number of PCI Expres	Server Server/Enterprise
Tcase	78 °C	Market segment Use conditions Maximum number of PCI Expres lanes	Server Server/Enterprise ss80
-		Market segment Use conditions Maximum number of PCI Expres lanes PCI Express slots version	Server Server/Enterprise ss80 5.0
Tcase DTS Max	78 °C	Market segment Use conditions Maximum number of PCI Expres lanes	Server Server/Enterprise ss80
Tcase	78 °C	Market segment Use conditions Maximum number of PCI Expres lanes PCI Express slots version	Server Server/Enterprise ss80 5.0 AMX, SSE4.2, AVX, AVX 2.0,
Tcase DTS Max Graphics	78 °C 93 °C	Market segment Use conditions Maximum number of PCI Express lanes PCI Express slots version Supported instruction sets Scalability Embedded options available	Server Server/Enterprise ss80 5.0 AMX, SSE4.2, AVX, AVX 2.0, AVX-512
Tcase DTS Max Graphics On-board graphics card	78 °C 93 °C No	Market segment Use conditions Maximum number of PCI Express lanes PCI Express slots version Supported instruction sets Scalability Embedded options available Export Control Classification	Server Server/Enterprise ss80 5.0 AMX, SSE4.2, AVX, AVX 2.0, AVX-512 2S
Tcase DTS Max Graphics On-board graphics card Discrete graphics card	78 °C 93 °C No No	Market segment Use conditions Maximum number of PCI Express lanes PCI Express slots version Supported instruction sets Scalability Embedded options available Export Control Classification Number (ECCN)	Server Server/Enterprise 5.0 AMX, SSE4.2, AVX, AVX 2.0, AVX-512 2S Yes 5A992C
Tcase DTS Max Graphics On-board graphics card	78 °C 93 °C No	Market segment Use conditions Maximum number of PCI Express lanes PCI Express slots version Supported instruction sets Scalability Embedded options available Export Control Classification Number (ECCN) Commodity Classification	Server Server/Enterprise ss80 5.0 AMX, SSE4.2, AVX, AVX 2.0, AVX-512 2S Yes
Tcase DTS Max Graphics On-board graphics card Discrete graphics card On-board graphics card	78 °C 93 °C No No Not available	Market segment Use conditions Maximum number of PCI Express lanes PCI Express slots version Supported instruction sets Scalability Embedded options available Export Control Classification Number (ECCN)	Server Server/Enterprise 5.0 AMX, SSE4.2, AVX, AVX 2.0, AVX-512 2S Yes 5A992C

Processor

Processor manufacturer	Intel
Processor generation	Intel Xeon Scalable 4th Gen
Processor model	4410Y
Processor base frequency	2 GHz
Processor family	Intel Xeon Silver
Processor cores	12
Processor socket	LGA 4677 (Socket E)
Processor threads	24
System bus rate	16 GT/s
Processor boost frequency	3.9 GHz
Processor cache	30 MB
Thermal Design Power (TDP)	150 W
Box	No
Stepping	S3
Processor codename	Sapphire Rapids
Processor ARK ID	232376

Processor special features

Intel® Hyper Threading Technology (Intel® HT Technology)	Yes
Intel® Turbo Boost Technology	2.0
Intel® AES New Instructions (Intel® AES-NI)	Yes
Intel Trusted Execution Technology	Yes

Intel® Speed Shift Technology	Yes
Intel® Transactional	Yes
Synchronization Extensions	
Intel® Total Memory Encryption	Yes
Intel ® Control-flow Enforcement	Yes
Technology (CET)	
Intel® Crypto Acceleration	Yes
Intel® Platform Firmware	Yes
Resilience Support	
Maximum Enclave Size Support	64 GB
for Intel® SGX	
Intel VT-x with Extended Page	Yes
Tables (EPT)	
Intel® OS Guard	Yes
Intel Software Guard Extensions	Yes
(Intel SGX)	
Intel 64	Yes
Intel Virtualization Technology	Yes
(VT-x)	
Intel Virtualization Technology for	rYes
Directed I/O (VT-d)	
AVX-512 Fused Multiply-Add	2
(FMA) units	
Intel® Boot Guard	Yes
Intel® Deep Learning Boost	Yes
(Intel® DL Boost) on CPU	
Intel	Yes
Performance Profile (Intel® SST-	
PP)	
Intel [®] Resource Director	Yes
Technology (Intel® RDT)	
Mode-based Execute Control	Yes
(MBE)	
Intel® QuickAssist Software	Yes
Acceleration	
Intel® On Demand Feature	Yes
Activation	
Intel® Data Streaming	1 default devices
Accelerator (DSA)	
Intel® Advanced Matrix	Yes
Extensions (AMX)	

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.