

# Broadcom MegaRAID SAS 9361-4i RAID controller

---



**Artikel** 428004  
**Herstellernummer** 05-25420-10  
**EAN** 0830343003051  
**Hersteller** Broadcom

Datacenter, cloud and high-performance computing environments not only require large amounts of storage capacity, they also must provide the data protection and performance today's applications and end users demand. The MegaRAID SAS 9361-4i 12Gb/s SAS and SATA RAID controller card addresses these needs by delivering proven performance and RAID data protection for a range of server storage applications.

## Zusammenfassung

---

Datacenter, cloud and high-performance computing environments not only require large amounts of storage capacity, they also must provide the data protection and performance today's applications and end users demand. The MegaRAID SAS 9361-4i 12Gb/s SAS and SATA RAID controller card addresses these needs by delivering proven performance and RAID data protection for a range of server storage applications.

Broadcom MegaRAID SAS 9361-4i, SAS, Serial ATA, PCI Express x8, 0, 1, 5, 6, 10, 50, 60, 12 Gbit/s, 1024 MB, DDR3

Broadcom MegaRAID SAS 9361-4i. Supported storage drive interfaces: SAS, Serial ATA, Host interface: PCI Express x8. RAID levels: 0, 1, 5, 6, 10, 50, 60, Data transfer rate: 12 Gbit/s, Internal memory: 1024 MB. Voltage: 3.3, 12 V. Width: 176.6 mm, Depth: 64.4 mm

## Merkmale

---

### Logistics data

Harmonized System (HS) code 84733080

### Weight & dimensions

Width	176.6 mm
Depth	64.4 mm

### Power

Voltage 3.3, 12 V

### Ports & interfaces

Supported storage drive interfaces	SAS, Serial ATA
Host interface	PCI Express x8
PCI Express slots version	3.0
Internal SAS ports	4

### System requirements

Windows operating systems supported Y

### Performance

Linux operating systems supported Y

RAID levels	0, 1, 5, 6, 10, 50, 60
-------------	------------------------

RAID Level Migration	Y
Data transfer rate	12 Gbit/s
SSD support	Y
Internal memory	1024 MB
Internal memory type	DDR3
Memory clock speed	1866 MHz
S.M.A.R.T. support	Y
Number of devices supported	128
Online Capacity Expansion	Y
Mean time between failures (MTBF)	1343187 h
Compatible products	EN55022, EN55024, EN60950, EN 61000-3-2, EN 61000-3-3; FCC Class A, Class B; UL1950; UL; CSA C22.2; VCCI; RRL for MIC; BSMI; C-tick

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.