

# Thermaltake TH240 ARGB Sync Snow Edition

---



**Artikel**  
**Herstellernummer**  
**EAN**  
Thermaltake

491390  
CL-W301-PL12SW-A  
0841163076583

## TH240 ARGB SyncSnow Edition AIO Liquid Cooler

TH240 ARGB Sync Snow Edition is an all-in-one liquid cooler which includes two 120mm powerful high static pressure fans, and a high performance radiator along with a water block, 16.8M RGB color lumination with pre-set lighting modes via the smart fan controller, or synchronize with motherboard RGB software for stunning RGB colors.

### Tt LCS Certified

Tt LCS Certified is a Thermaltake exclusive certification applied only to products that pass the design and hardcore enthusiast standards. The Tt LCS certification is to ensure you will get the best performance from the best features and fitment.

### Smart Fan Controller

The ARGB controller allows users to switch LED modes, LED colors, and lighting speeds when using a motherboard without a 5V addressable RGB header. Users can switch between flow, ripple, pulse, blink, wave, full light, RGB spectrum, and off modes with various colors and LED speed options.

### Dual 120mm AR G B Radiator Fan

High-static pressure fan design delivers impressive cooling performance.

### High Efficiency Radiator

Specially designed 240mm large surface radiator increases surface delivering exceptional heat dissipation.

### High Performance Waterblock

The high performance copper base plate accelerates heat conductivity.

### High Reliability Pump

The high quality and reliable pump enables maximum water circulation, keeping the copper plate continuously cool. The low evaporation tube effectively decreases the loss of coolant; therefore no refill is either needed or required.

### Simple Setup

Featuring superb cooling performance, the TH240 Snow Edition provides an easy installation and maintenance-free operation, requiring only the minimum amount of space in the chassis.

## Zusammenfassung

---

### TH240 ARGB SyncSnow Edition AIO Liquid Cooler

TH240 ARGB Sync Snow Edition is an all-in-one liquid cooler which includes two 120mm powerful high static pressure fans, and a high performance radiator along with a water block, 16.8M RGB color lumination with pre-set lighting modes via the smart fan controller, or synchronize with motherboard RGB software for stunning RGB colors.

Tt LCS Certified

Tt LCS Certified is a Thermaltake exclusive certification applied only to products that pass the design and hardcore enthusiast standards. The Tt LCS certification is to ensure you will get the best performance from the best features and fitment.

Smart Fan Controller

The ARGB controller allows users to switch LED modes, LED colors, and lighting speeds when using a motherboard without a 5V addressable RGB header. Users can switch between flow, ripple, pulse, blink, wave, full light, RGB spectrum, and off modes with various colors and LED speed options.

Dual 120mm AR G B Radiator Fan

High-static pressure fan design delivers impressive cooling performance.

High Efficiency Radiator

Specially designed 240mm large surface radiator increases surface delivering exceptional heat dissipation.

High Performance Waterblock

The high performance copper base plate accelerates heat conductivity.

High Reliability Pump

The high quality and reliable pump enables maximum water circulation, keeping the copper plate continuously cool. The low evaporation tube effectively decreases the loss of coolant; therefore no refill is either needed or required.

Simple Setup

Featuring superb cooling performance, the TH240 Snow Edition provides an easy installation and maintenance-free operation, requiring only the minimum amount of space in the chassis.

Thermaltake TH240 ARGB Sync Snow Edition, All-in-one liquid cooler

Thermaltake TH240 ARGB Sync Snow Edition. Type: All-in-one liquid cooler, Maximum air pressure: 1.31 mmH2O

Merkmale

		Design	
Logistics data		Number of fans	2 fan(s)
Harmonized System (HS) code	84733080	Fan connector	3-pin
		Water block material	Copper
Other features		Weight & dimensions	
Tube material	Rubber	Radiator width	27.3 cm
		Radiator depth	12 cm
		Radiator height	2.7 cm
		Tube length	40 cm
		Fan dimensions (W x D x H)	120 x 120 x 25 mm
Power		Performance	
Pump voltage	12/5 V	Suitable location	Processor
Fan current	0.38 A	Type	All-in-one liquid cooler
		Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM1, Socket FM2

Maximum airflow	59.28 cfm
Maximum air pressure	1.31 mmH2O
Fan noise level (max)	28.2 dB
Pump motor speed (max)	3300 RPM
Fan speed (max)	1500 RPM

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.