

Ubiquiti Networks POE-24-24W PoE adapter



Artikel	603153
Herstellernummer	POE-24-24W
EAN	0810354021206
Ubiquiti Networks	

Device Protection

PoE Adapters are highly reliable, and when used with Ubiquiti TOUGH Cable, they provide earth grounding and surge protection to help protect against electrostatic discharge (ESD) events.

Seamless airGateway Compatibility

The 15V, 0.8A and 24V, 0.5A models, POE-15-12W, POE-24-12W and POE-24-12W-G, work with the airGateway to bridge airMAX connections to Wi-Fi at customer locations.

Zusammenfassung

Device Protection

PoE Adapters are highly reliable, and when used with Ubiquiti TOUGH Cable, they provide earth grounding and surge protection to help protect against electrostatic discharge (ESD) events.

Seamless airGateway Compatibility

The 15V, 0.8A and 24V, 0.5A models, POE-15-12W, POE-24-12W and POE-24-12W-G, work with the airGateway to bridge airMAX connections to Wi-Fi at customer locations.

Ubiquiti Networks POE-24-24W, Black, 24 V, 100 - 240 V, 50/60 Hz, 0.4 - 0.6 A, 1 A

Ubiquiti Networks POE-24-24W. Product colour: Black. Power over Ethernet (PoE) voltage: 24 V, Input voltage: 100 - 240 V, Input frequency: 50/60 Hz. Width: 57 mm, Depth: 88 mm, Height: 33 mm

Merkmale

Logistics data

Harmonized System (HS) 85044090

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating temperature (T-T)	32 - 104 °F
Operating relative humidity (H-H)	35 - 95%

code

Storage temperature (T-T) -30 - 70 °C

Network

Power over Ethernet (PoE) Y

Features

Product colour Black

Surge protection Y

Ports & interfaces

Ethernet LAN (RJ-45) ports 2

RJ-45 input ports 1

RJ-45 output ports 1

Power

Power over Ethernet (PoE) voltage 24 V

Input voltage 100 - 240 V

Input frequency 50/60 Hz

Input current 0.4 - 0.6 A

Output current 1 A

Weight & dimensions

Width 57 mm

Depth 88 mm

Height 33 mm

Weight 135 g

Dimensions (WxDxH) 88 x 57 x 33 mm

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.