

# Ubiquiti Networks POE-24-12W

---



<b>Artikel</b>	603154
<b>Herstellernummer</b>	POE-24-12W(EU)
<b>EAN</b>	0810354022982
Ubiquiti Networks	

## Device Protection

PoE Adapters are highly reliable, and when used with Ubiquiti TOUGH Cable™, they provide earth grounding and surge protection to help protect against electrostatic discharge (ESD) events.

## Convenient Wall-Mounting

The 24V, 0.5A models, POE-24-12W and POE-24-12W-G, are wall-mountable using the optional wall-mount brackets.

## Seamless airGateway™ Compatibility

The 15V, 0.8A and 24V, 0.5A models, POE-15-12W, POE-24-12W and POE-24-12W-G, work with the airGateway™ to bridge airMAX® connections to Wi-Fi at customer locations.

## Zusammenfassung

---

### Device Protection

PoE Adapters are highly reliable, and when used with Ubiquiti TOUGH Cable™, they provide earth grounding and surge protection to help protect against electrostatic discharge (ESD) events.

### Convenient Wall-Mounting

The 24V, 0.5A models, POE-24-12W and POE-24-12W-G, are wall-mountable using the optional wall-mount brackets.

### Seamless airGateway™ Compatibility

The 15V, 0.8A and 24V, 0.5A models, POE-15-12W, POE-24-12W and POE-24-12W-G, work with the airGateway™ to bridge airMAX® connections to Wi-Fi at customer locations.

Ubiquiti Networks POE-24-12W, CE, FCC, IC, UL, 24 V, 100 - 240 V, 50/60 Hz, 0 - 40 °C, 32 - 104 °F

Ubiquiti Networks POE-24-12W. Certification: CE, FCC, IC, UL. Power over Ethernet (PoE) voltage: 24 V, Input voltage: 100 - 240 V, Input frequency: 50/60 Hz. Width: 44 mm, Depth: 29 mm, Height: 87 mm. Number of products included: 1 pc(s)

## Merkmale

---

### Features

### Ports & interfaces

Ethernet LAN (RJ-45) ports	2
----------------------------	---

Certification	CE, FCC, IC, UL
---------------	-----------------

### Logistics data

Harmonized System (HS) code	85044090
-----------------------------	----------

### Network

Power over Ethernet (PoE)	Y
---------------------------	---

### Packaging content

Number of products included	1 pc(s)
-----------------------------	---------

### Power

Power over Ethernet (PoE) voltage	24 V
Input voltage	100 - 240 V
Input frequency	50/60 Hz

### Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating temperature (T-T)	32 - 104 °F
Operating relative humidity (H-H)	35 - 95%
Storage temperature (T-T)	-30 - 70 °C

### Weight & dimensions

Width	44 mm
Depth	29 mm
Height	87 mm
Weight	92 g

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.