

APC Back-UPS uninterruptible power supply (UPS)



Artikel	65015
Herstellernummer	BK350EI
EAN	0731304016342
APC	

This product is part of the Back-UPS range. The BK350EI features a total of 6 power outlets, 5 of which are UPS battery backup and one that is surge only. Its runtime at 100W is 14 minutes 52 seconds. It provides data line protection with a RJ45 analog phone line for phone or fax or modem or DSL. Its dimensions are 16.5 x 9.1 x 28.4 cm and 6.32kg. The BK350EI ensures office systems and their valuable data are protected from dangerous power surges, spikes and blackouts.

Zusammenfassung

This product is part of the Back-UPS range. The BK350EI features a total of 6 power outlets, 5 of which are UPS battery backup and one that is surge only. Its runtime at 100W is 14 minutes 52 seconds. It provides data line protection with a RJ45 analog phone line for phone or fax or modem or DSL. Its dimensions are 16.5 x 9.1 x 28.4 cm and 6.32kg. The BK350EI ensures office systems and their valuable data are protected from dangerous power surges, spikes and blackouts.

APC Back-UPS, 350VA/210W, Tower, 230V, 4x IEC C13 Outlets , User Replaceable Battery, Standby (Offline), 0.35 kVA, 210 W, 180 V, 266 V, 50/60 Hz

APC Back-UPS, 350VA/210W, Tower, 230V, 4x IEC C13 Outlets , User Replaceable Battery. UPS topology: Standby (Offline), Output power capacity: 0.35 kVA, Output power: 210 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 7 Ah, Battery capacity: 116 VAh. Form factor: Tower, Product colour: Beige, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: C-tick, CE, EN 50091-1, EN 50091-2,GOST, VDE, PEP, EOLI

Merkmale

Sustainability

Sustainability certificates	ENERGY STAR, Green Premium
-----------------------------	----------------------------

Weight & dimensions

Width	91 mm
Depth	284 mm
Height	165 mm
Weight	6.32 kg

Certificates

Compliance certificates	RoHS
-------------------------	------

Ports & interfaces

AC outlet types	C13 coupler
-----------------	-------------

Certification	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, PEP, EOLI
---------------	----------------------------------------------------------

Power plug	C14 coupler
AC outlets quantity	4 AC outlet(s)
Number of output IEC jumpers	2
USB port	Yes

Logistics data

Products per pallet	48 pc(s)
Harmonized System (HS) code	85078000

Packaging content

Cables included	Phone (RJ-11), USB cable
Quick installation guide	Yes

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V
Filtering	Yes

Design

Form factor	Tower
Cable length	1.83 m
Product colour	Beige
LED indicators	Battery replacement

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Packaging data

Warranty card	Yes
Software CD	Yes
Bundled software	PowerChute Personal Edition
Package width	241 mm
Package depth	368 mm
Package height	178 mm
Package weight	7.05 kg

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	7 Ah
Battery capacity	116 VAh
Battery voltage	12 V
Typical backup time at full load	8.6 min
Typical backup time at half load	22.1 min
Battery life (max)	6 year(s)
Battery recharge time	6 h
Automatic battery test	Yes

Features

UPS topology	Standby (Offline)
Output power capacity	0.35 kVA
Output power	210 W
Input operation voltage (min)	180 V
Input operation voltage (max)	266 V
Input frequency	50/60 Hz
Output frequency regulation	47 - 63 Hz
Maximum current	7 A
Surge energy rating	310 J
Hold time (min)	6 ms
Hold time (max)	10 ms
Efficiency	98.6%
Surge protection	Yes
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Telephone
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Low battery alarm, Overload alarm