FSP/Fortron HP2-600 power supply unit



Artikel Herstellernummer EAN FSP/Fortron 703187 PPA6005605 4713224525957

The new Hydro K PRO PSUs comply fully ATX12 v2.52 standard and the latest safety 62368 regulation as well and comes with highgrade ribbon cables, give your PC a polished look. The Hydro K PRO series is designed as a powerful single +12V rail that continually delivers maximum performance for the most demanding graphic cards, while FSP's custom DC-DC design provides safety and power efficiency. Besides, with an 230V 80 Plus® rating, delivers over 88% high efficiency and low noise levels thanks to its hydraulic bearing fan design, where a large 120mm fan takes care of cooling duties when required, making it excellent for situations that are sensitive to size and noise.

Up-to-date Circuit Design

A dual forward topology integrated with active PFC and PWM technology and double EMI filter delivers full power and enhance stability to your system.

Stable DC to DC Output Quality

DC to DC modules with low ripple noise and prolongs system lifetime.

Double Layer EMI Filter

To reduce electromagnetic interference and suppress noise.

Low Noise, Less Heat

Hydro K PRO series is equipped with the 120mm hydraulic bearing fan (HYB) which makes optimum cooling and reduces noise. Moreover, the lifespan of fan is longer than standard one.

+12V Single Rail Design

Designed for power-intensive VGA cards, provides strong power to any overloading condition.

80 Plus® Bronze Certification

With an 230V 80 Plus® rating, Hydro K PRO series delivers over 88% high efficiency.

Energy Related ErP/Eup 2013

Green Power! The total AC power consumption less than 5Vsb rail to meet the new EU Regulation ErP 2013 for modern systems.

Zusammenfassung

The new Hydro K PRO PSUs comply fully ATX12 v2.52 standard and the latest safety 62368 regulation as well and comes with highgrade ribbon cables, give your PC a polished look. The Hydro K PRO series is designed as a powerful single +12V rail that continually delivers maximum performance for the most demanding graphic cards, while FSP's custom DC-DC design provides safety and power efficiency. Besides, with an 230V 80 Plus® rating, delivers over 88% high efficiency and low noise levels thanks to its hydraulic bearing fan design, where a large 120mm fan takes care of cooling duties when required, making it excellent for situations that are sensitive to size and noise.

Up-to-date Circuit Design

A dual forward topology integrated with active PFC and PWM technology and double EMI filter delivers full power and enhance stability to your system.

Stable DC to DC Output Quality

DC to DC modules with low ripple noise and prolongs system lifetime.

Double Layer EMI Filter

To reduce electromagnetic interference and suppress noise.

Low Noise, Less Heat

Hydro K PRO series is equipped with the 120mm hydraulic bearing fan (HYB) which makes optimum cooling and reduces noise. Moreover, the lifespan of fan is longer than standard one.

+12V Single Rail Design

Designed for power-intensive VGA cards, provides strong power to any overloading condition.

80 Plus® Bronze Certification

With an 230V 80 Plus® rating, Hydro K PRO series delivers over 88% high efficiency.

Energy Related ErP/Eup 2013

Green Power! The total AC power consumption less than 5Vsb rail to meet the new EU Regulation ErP 2013 for modern systems.

FSP/Fortron HP2-600, 600 W, 200 - 240 V, 50 - 60 Hz, 4.5 A, Active, 100 W

FSP/Fortron HP2-600. Total power: 600 W, AC input voltage: 200 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 24-pin ATX, Cabling type: Semi-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 140 mm, Depth: 150 mm, Height: 86 mm

Merkmale

		Design		
Packaging data		Product colour	Black	
Paakaga tupo	Box	Cooling type	Active	
Package type	DUX	Fan diameter	12 cm	
		Number of fans	1 fan(s)	
		On/off switch	Y	
Weight & dimens	ions			
Width	140 mm	Ports & interfaces	Ports & interfaces	
Depth	150 mm	Forts & Interlaces		
Height	86 mm	Motherboard power connector	24-pin ATX	

Performance

80 PLUS certification	80 PLUS Bronze			
Purpose	PC			
Power supply unit (PSU) form ATX factor				
Bearing technology	HYB			

Motherboard power connector	24-pin ATX
Number of SATA power	5
connectors	
Peripheral (Molex) power	2
connectors (4-pin)	
PCI Express power connectors	2
(6+2 pin)	
CPU power connector (4+4 pin)	Y
Floppy drive power connector	1
Floppy disk drive connector	Y
Cabling type	Semi-Modular

Power

600 W
200 - 240 V
50 - 60 Hz
4.5 A

Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (+12V)	600 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	12.5 W
Max output current (+3.3V)	20 A
Max output current (+12V)	50 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	2.5 A
Efficiency	88%
Power protection features	Over current, Over power, Over voltage, Short circuit

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.