

FSP/Fortron FlexGURU 300W power supply unit

Artikel	703209
Herstellernummer	PPA3004300
EAN	4713224522529
FSP/Fortron	



FSP's FlexGURU Flex ATX models are available in standard direct output and modular cable configurations, which includes the most updated modular model selections in the market. The modular design improves the ease of nstallation, users can configure their connector cables according to the system needs. The special plug-in design for cables and jacks improves the convenience of replacement. Fully modular connectors allow users to quickly disassemble cables, pinpoint issues and save debugging time whenever the system experiences problems.

Zusammenfassung

FSP's FlexGURU Flex ATX models are available in standard direct output and modular cable configurations, which includes the most updated modular model selections in the market. The modular design improves the ease of nstallation, users can configure their connector cables according to the system needs. The special plug-in design for cables and jacks improves the convenience of replacement. Fully modular connectors allow users to quickly disassemble cables, pinpoint issues and save debugging time whenever the system experiences problems.

FSP/Fortron FlexGURU 300W, 300 W, 100 - 240 V, 50 - 60 Hz, 6-3 A, Active, 90%

FSP/Fortron FlexGURU 300W. Total power: 300 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX. Purpose: Server, Power supply unit (PSU) form factor: Flex ATX, Mean time between failures (MTBF): 100000 h. Product colour: Black, Fan diameter: 4 cm, Number of fans: 40 fan(s). Width: 150 mm, Depth: 81.5 mm, Height: 40.5 mm

Merkmale

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------

Design

Product colour	Black
Fan diameter	4 cm

Weight & dimensions

Width	150 mm
Depth	81.5 mm
Height	40.5 mm

Ports & interfaces

Motherboard power connector	20+4 pin ATX
Number of SATA power connectors	4

Number of fans	40 fan(s)
----------------	-----------

Peripheral (Molex) power connectors (4-pin)	2
CPU power connector (4+4 pin)	Y
Floppy drive power connector	1
Floppy disk drive connector	Y

Performance

Purpose	Server
Power supply unit (PSU) form factor	Flex ATX
Mean time between failures (MTBF)	100000 h

Power

Total power	300 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	6-3 A
Power Factor Correction (PFC) type	Active
Efficiency	90%
Power protection features	Over current, Over power, Short circuit, Under voltage

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.