

# Ubiquiti Networks POE-48-24W-G



<b>Artikel</b>	777260
<b>Herstellernummer</b>	POE-48-24W-G EU
<b>EAN</b>	0810354023088
Ubiquiti Networks	

Electrostatic discharge (ESD) is the leading cause for outdoor device failures. You can effectively protect against ESD damage using a grounded Ubiquiti PoE Adapter, TOUGH Cable™, and TOUGH Cable Connectors.

## Zusammenfassung

Electrostatic discharge (ESD) is the leading cause for outdoor device failures. You can effectively protect against ESD damage using a grounded Ubiquiti PoE Adapter, TOUGH Cable™, and TOUGH Cable Connectors.

Ubiquiti Networks POE-48-24W-G, Gigabit Ethernet, 10,100,1000 Mbit/s, Black, CE, FCC, IC, UL, 48 V, 100 - 240 V

Ubiquiti Networks POE-48-24W-G. Ethernet interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Black, Certification: CE, FCC, IC, UL. Power over Ethernet (PoE) voltage: 48 V, Input voltage: 100 - 240 V, Input frequency: 50/60 Hz. Width: 96 mm, Depth: 62 mm, Height: 35 mm. Number of products included: 1 pc(s)

## Merkmale

### Logistics data

Harmonized System (HS) code 85044095

### Packaging content

Number of products included 1 pc(s)

### Ports & interfaces

Ethernet LAN (RJ-45) ports 2

### Network

Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Y

### Power

Power over Ethernet (PoE) voltage	48 V
Input voltage	100 - 240 V
Input frequency	50/60 Hz

### Operational conditions

Operating temperature (T-T) 0 - 40 °C

## Features

Product colour	Black
Certification	CE, FCC, IC, UL

Operating temperature (T-T)	32 - 104 °F
Operating relative humidity (H-H)	35 - 95%
Storage temperature (T-T)	-30 - 70 °C

## Weight & dimensions

Width	96 mm
Depth	62 mm
Height	35 mm
Weight	166 g

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.