Honeywell Voyager 1400g



Artikel Herstellernummer EAN Honeywell 789544 1400G2D-2USB-1 5711045754609

Voyager 1400g

Bar codes are becoming increasingly popular across a wide range of industries for a number of reasons. Some enterprises have a desire to capture large amounts of data, despite space constraints, while others are being required to read bar codes due to government regulations or supplier mandates. And an even larger group of enterprises simply have the desire to leverage emerging trends that require area-imaging technology, today or in the future, without needing to purchase additional scanning hardware.

Reliable Data Collection: Offers omnidirectional reading of virtually all linear bar codes and the most widely used bar codes, including poor quality and mobile bar codes.

Remote MasterMindTM Ready: Reduces total cost of ownership by providing a turnkey remote device management solution that easily manages and tracks usage of installed devices.

Future Proof: Delivers affordable scanning of 2D bar codes, allowing enterprises to meet their current and future bar code scanning needs with a single device.

Flexible Licensing Solution: Meets diverse scanning requirements by offering models with basic functionality—purchase software licenses to enable additional functionality as the need arises.

Zusammenfassung

Voyager 1400g

Bar codes are becoming increasingly popular across a wide range of industries for a number of reasons. Some enterprises have a desire to capture large amounts of data, despite space constraints, while others are being required to read bar codes due to government regulations or supplier mandates. And an even larger group of enterprises simply have the desire to leverage emerging trends that require area-imaging technology, today or in the future, without needing to purchase additional scanning hardware.

Reliable Data Collection: Offers omnidirectional reading of virtually all linear bar codes and the most widely used bar codes, including poor quality and mobile bar codes.

Remote MasterMindTM Ready: Reduces total cost of ownership by providing a turnkey remote device management solution that easily manages and tracks usage of installed devices.

Future Proof: Delivers affordable scanning of 2D bar codes, allowing enterprises to meet their current and future bar code scanning needs with a single device.

Flexible Licensing Solution: Meets diverse scanning requirements by offering models with basic functionality—purchase software licenses to enable additional functionality as the need arises.

Honeywell Voyager 1400g, Handheld bar code reader, 1D/2D, PDF417, 0 - 100000 lx, 0 - 60°, Wired

Honeywell Voyager 1400g. Type: Handheld bar code reader, Scanner type: 1D/2D, 2D (matrix & stacked) barcodes supported: PDF417. Connectivity technology: Wired, Standard interfaces: USB, Cable length: 1.5 m. Product colour: Black, International Protection (IP) code: IP42. Power consumption (standby): 0.45 W, Input voltage: 4 - 5.5 V, Power consumption: 400 mA. Weight: 119 g, Width: 66 mm, Depth: 180 mm

Merkmale

| Logistics data | | |
|------------------------|----------|--|
| Harmonized System (HS) | 84716070 | |

Performance

| International Protection (IP) | IP42 |
|-------------------------------|-------|
| code | |
| Product colour | Black |

Operational conditions

| Operating temperature (T-T) | 0 - 40 °C | |
|--|-------------|--|
| Storage temperature (T-T) | -40 - 60 °C | |
| Operating relative humidity (H-0 - 95% | | |
| H) | | |

Ports & interfaces

| Connectivity technology | Wired |
|-------------------------|-------|
| Standard interfaces | USB |
| Cable length | 1.5 m |

| rowei |
|-------|
|-------|

| Power consumption (standby) | 0.45 W |
|-----------------------------|-----------|
| Input voltage | 4 - 5.5 V |
| Power consumption | 400 mA |

Weight & dimensions

| Width | 66 mm |
|--------|--------|
| Depth | 180 mm |
| Height | 43 mm |
| Weight | 119 g |

Scanning

| Type | Handheld bar code reader |
|--|--------------------------|
| Optical sensor resolution | 640 pixels |
| Scanner type | 1D/2D |
| 2D (matrix & stacked) barcodes supported | PDF417 |
| Light levels (direct sunlight) | 0 - 100000 lx |
| Pitch reading angle | 0 - 60° |

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.