

# Digitus DK-1644-A-020 networking cable

---

<b>Artikel</b>	820525
<b>Herstellernummer</b>	DK-1644-A-020
<b>EAN</b>	4016032327370
Digitus	



Future-oriented standards and high-end quality for your network.

- With LSZH (Low Smoke Zero Halogen) sheath for best fire behaviour and low smoke emissions.
- Transparent yellow colored plug with metal shielding for easy identification of Category 6A (500 MHz)
- Conductor: Copper (Cu)
- PoE+ ready

The DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

## Zusammenfassung

---

Future-oriented standards and high-end quality for your network.

- With LSZH (Low Smoke Zero Halogen) sheath for best fire behaviour and low smoke emissions.
- Transparent yellow colored plug with metal shielding for easy identification of Category 6A (500 MHz)
- Conductor: Copper (Cu)
- PoE+ ready

The DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

Digitus CAT 6A S/FTP patch cord, 2 m, Cat6a, S/FTP (S-STP), RJ-45, RJ-45

Digitus CAT 6A S/FTP patch cord. Cable length: 2 m, Cable standard: Cat6a, Cable shielding: S/FTP (S-STP), Connector 1: RJ-45, Connector 2: RJ-45

## Merkmale

---

### Operational conditions

Operating temperature (T-T) -20 - 60 °C

### Other features

Quantity 1

### Logistics data

Harmonized System (HS) code 84733080  
UK Trade Tariff code 85444210

### Packaging data

Package width 140 mm  
Package depth 16 mm  
Package weight 86 g  
Package volume 560 cm<sup>3</sup>  
Package type Polybag

### Features

Product colour Grey  
Cable length 2 m  
Cable standard Cat6a  
Cable shielding S/FTP (S-STP)  
Connector 1 RJ-45  
Connector 2 RJ-45  
Connector 1 gender Male  
Connector 2 gender Male  
Jacket material Low smoke zero halogen (LSZH)  
AWG wire size 26/7  
Certification IEC 60332-1, IEC 60332-3, IEC 61034  
Country of origin China

Preisänderungen und Irrtümer vorbehalten. Alle Produkte solange der Vorrat reicht.